


FMTV M1148 A1P2

9.0 ton Load Handling System


The Family of Medium Tactical Vehicles (FMTV) provides the U.S. Army's backbone for tactical unit mobility and logistics support throughout the battlefield. These vehicles are considered the most sophisticated off-road, multi-purpose military tactical vehicles in use, and are capable of operating worldwide on primary and secondary roads, as well as on trails and cross-country in weather extremes from -50°F (-46°C) to +120°F (49°C). The new Long Term Armor Strategy (LTAS) cab is capable of accepting appliqué armor for ballistic protection.

Product Numbers
NSN 2320-01-508-8859



FMTV A1P2 KEY FEATURES

- Full-time all-wheel drive
- Fully automatic transmission
- Electronic Central Tire Inflation System (CTIS)
- Anti-lock Braking System (ABS)
- Interactive Electronic Technical Manuals (IETM)
- Fully MANPRINT compliant
- Configurable for C-130 air transport
- U.S. Army proven ultra-reliability
- Family of 16+ vehicles with 80% commonality
- Designed for 22-year corrosion protection
- Highest proven reliability of any tactical vehicle
- Optional Electronic Stability Control
- Air Conditioning



FMTV M1148 A1P2

9.0 ton Load Handling System

VEHICLE SPECIFICATIONS

Length:	370 in (9,396 mm)
Width:	94.5 in (2,401 mm)
Height:	
Operational	111.4 in (2,829 mm)
For Air Transport	105.5 in (2,680 mm)
Height-Pintle:	
Unloaded	36 in (905 mm)
With Payload	33 in (839 mm)
Wheel Base:	209 in (5,300 mm)
Ground Clearance:	
Loaded	22 in (559 mm)
Under Axle	14.4 in (365 mm)
Approach/Departure Angle:	40°/23°
Vehicle Curb Weight with Fuel & Crew:	28,781 lb (13,082 kg)
Payload, Lift Capacity:	17,640 lb (8,000 kg) plus kits
Towed Load, LHS Trailer:	27,117 lb (12,300 kg)
Maximum Speed:	
Governed, at Gross Weight	58 mph (94 km/h)
Range, 76 gal (295 L) nominal:	300+ mi (483+ km)
Maximum Grade/Side Slope:	60%/30%
Turning Circle:	
Curb-to-Curb	77 ft (23.5 m)
Wall-to-Wall	83 ft (25.3 m)
Fording, without Kit:	30 in (762 mm)

EQUIPMENT SPECIFICATIONS

LTAS Cab:	
Design	Capable of accepting appliqué armor 3-Man, Ergonomically Adjustable Driver Seat and Steering Wheel
Steering Storage	Power Assisted, Recirculating Ball 8 cu ft
Engine:	
Caterpillar C7	Heavy Duty Diesel, 6-Cylinder, Electronic Controlled, Fuel-Injected Turbocharged and Aftercooled, EPA Certified
Rating	330 hp (246 kW) @ 2400 rpm
Displacement	441 cu in (7.2 L)
Torque	860 lb-ft (1,166 Nm) @ 1440 rpm
Fuel	Diesel, DF-2, JP-4, JP-8, VV-F-800
Oil	MIL-L-2104D, MIL-L-46167, 22 qt (21 L)
Transmission:	
Allison 3700SP	Automatic/Select 7-speed, Electronically Controlled
Full-Time All-Wheel Drive	Integral Transfer Case
Normal Operation	30% Torque Front Wheels, 70% Torque Rear Wheels; Off-Road, Equal Front and Rear
Oil	DEXRON VI ATF, 31.8 qt (30 L)
Axles:	
ArvinMeritor	Front, Intermediate and Rear Axles
Carrier	Single Reduction, Amboid-Gearing
Wheel End	Bevel Wheel End Reduction, Ratio 2:1
Overall Axle Gear Ratio	7.8:1
Front Axle Steering Angle	35°
Electrical:	
System	12/24 volt, EMI/HAEMP Qualified, Resettable Circuit Breakers, Central Power Distribution Panel, Battery and Charging Management System
Alternator	260 amp, 12/24 volt, Waterproof, EMI/RFI Suppressed
Starter	24 volt Waterproof
Instrumentation	SAE J1708 Data Bus Driven Instrument Cluster
Tires:	Goodyear 395/85R20 MV/T

Brakes:	
Primary	Dual-Circuit, Four Channel Air, Anti-Lock Braking System (ABS) Front: Air/Hydraulic, Rear: Air with Trailers ABS Connectors for Emergency Towing
Supplemental	Air Actuated, Driver Controlled Exhaust Brake
Central Tire Inflation System, Eaton:	Cab-Mounted Electronic Controls, Operable while Driving, Highway, Cross-Country, Air Transport, Sand/Mud/Snow, and Emergency Modes
Diagnostics, Interactive Electronic Technical Manuals (IETM):	Class V, Intrusive Diagnostics, SAE J1708/J1939 Data Buses to Diagnose All (4) Unique Electronic Control Modules (ECM)
Suspension:	
Front	Parabolic-Tapered Leaf Spring with Coil over Hydraulic Shock Absorbers
Rear	Tandem Axles with Parabolic-Tapered Leaf Spring with Hydraulic Shock Absorbers and Stabilizer Bar
Transportability/Deployability:	
Internally	Air-transportable by C-130, C-141, C-17, and C-5A
Externally	Transportable by CH-53 Helicopter
Self Recovery Winch: (Optional)	15,500 lb (7,031 kg) Rating, 280 ft (85.3 m) Line Capacity, Fore/Aft Recovery Position
LHS Capabilities:	Load/Unload a 20 ft Container onto LHS or LHS Trailer; Allow 157.5 in (4 m) Clearance with 8 ft x 8 ft x 20 ft (2.4 m x 2.4 m x 6.1 m) ISO Container Mounted Compatible with U.S. Army Flatracks (M1, M3, M1077); Automatically Guides, Centers, and Secures Flatrack; Lift Frame is Stowed on the Vehicle

FOR MORE INFORMATION CONTACT:

BAE Systems
 5000 I-10 West
 Sealy, TX 77474 USA
 Telephone 281-856-0139
 Toll Free 800-221-3688
 Fax 979-885-7910
 Email sales.mhv@baesystems.com
 www.baesystems.com

This document gives only a general description of the product(s) or services and except where expressly provided otherwise shall not form part of any contract. From time to time, changes may be made in the products or the conditions of supply. BAE Systems reserves the right to change product specifications without prior notice.